

manner as Example 2. The result is as follows.

Table 3

Area of the applied part	Subject 1		Subject 2		Subject 3	
	Voltage (V)	Detection of detachment	Voltage (V)	Detection of detachment	Voltage (V)	Detection of detachment
0/10	0	L	0	L	0	L
2/10	1.6	L	1.6	L	1.5	L
4/10	2.7	L	2.6	L	2.6	L
6/10	3.7	L	3.6	L	3.5	L
8/10	4.2	L	4.2	L	4.1	L
10/10	4.8	H	4.8	H	4.7	H

5 The test was conducted in such a way that the output voltage was 5 V, and one of the areas of the device in contact with the applied part of the transdermal was varied from 0/10 to 10/10. The voltage on the output terminal 21 and the output signal 28 were measured 1 ms after the analog switch 20 was
10 opened. "L" of the output signal 28 (detection of detachment) indicates that conduction was abnormal and "H" represents that conduction was normal. From Table 3, the iontophoresis device according to Example 3 can detect detachment of the device encountered, even a small area, during the application.

15

INDUSTRIAL APPLICABILITY

The iontophoresis device according to the present invention can detect conduction states with high accuracy and is applicable to iontophoresis in the field of medical care.

20

CLAIMS

1. A device for iontophoresis supplying a drug to transdermal or transmucosal, comprising: first means for detecting a
5 capacitance stored in the transdermal or the transmucosal; and second means for determining a conduction state of current into the transdermal or the transmucosal based on the output detected by the first means.
2. The device for iontophoresis according to Claim 1, wherein
10 the first means is a detection circuit for a reactive current flowing through the transdermal or the transmucosal.
3. The device for iontophoresis according to Claim 1, wherein the first means is a detection circuit for a residual voltage developed in the transdermal or the transmucosal.
- 15 4. A method for determining an operation of an iontophoresis apparatus, wherein a capacitance stored in transdermal or transmucosal is detected to determine a conduction state of current flowing into the transdermal or the transmucosal.
5. The method for detecting an operation of an iontophoresis
20 apparatus according to Claim 4, wherein the detection of the capacitance is carried out by detecting a reactive current flowing through the transdermal or the transmucosal.
6. The method for detecting an operation of an iontophoresis apparatus according to Claim 4, wherein the detection of the
25 capacitance is carried out by detecting a residual voltage developed in the transdermal or the transmucosal.
7. An iontophoresis apparatus comprising: a preparation for

09990284-081301

iontophoresis, holding a drug; and a device for iontophoresis
having means for generating an electrical output to supply
a drug from the preparation into transdermal or transmucosal
and means for detecting a capacitance stored in the transdermal
5 or the transmucosal to determine a conduction state of a current
flowing into the transdermal or the transmucosal.

09390234.034301